

PRODUCT CODE

PRODUCT CODE X X X X X X - X X X X X X X X X X X X X X
 1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17 18

DIGIT 1 PRODUCT GROUP
 F = FRONT TWIN SHOCK V = FRONT MONO SHOCK
 R = REAR TWIN SHOCK M = REAR MONO SHOCK
 T = REAR TWIN SCOOTER SHOCK O = REAR MONO SCOOTER SHOCK
 I = INNER TUBE K = FRONT FORK
 E = STEERING DAMPER

DIGIT 2 PRODUCT TYPE
 S = SINGLE TUBE HYDRAULIC SHOCK D = DOUBLE TUBE HYDRAULIC SHOCK
 A = DIVIDED PISTON GAS SHOCK B = GAS-DTG
 T = TRIPLE PISTON (ATPD) Z = EMULSION GAS SHOCK (E = ECO LINE)
 G = TOP EXTERNAL RESERVOIR PIGGY BACK GAS SHOCK (C = ECO LINE)
 U = BOTTOM EXTERNAL RESERVOIR PIGGY BACK GAS SHOCK (K = ECO LINE)
 X = EXTERNAL RESERVOIR ON HOSE GAS SHOCK (O = ECO LINE)

DIGIT 3-6 PISTON AND SHAFT SIZE
 168 = PISTON 16 MM + SHAFT 8 MM. 364 = PISTON 36 MM + SHAFT 14 MM.
 188 = PISTON 18 MM + SHAFT 8 MM. 366 = PISTON 36 MM + SHAFT 16 MM.
 220 = PISTON 22 MM + SHAFT 10 MM. 456 = PISTON 45 MM + SHAFT 16 MM.
 222 = PISTON 22 MM + SHAFT 12 MM. 506 = PISTON 50 MM + SHAFT 16 MM.
 302 = PISTON 30 MM + SHAFT 12 MM. 3020 = PISTON 30 MM + SHAFT 20 MM.
 304 = PISTON 30 MM + SHAFT 14 MM. 6022 = PISTON 60 MM + SHAFT 22 MM.
 306 = PISTON 30 MM + SHAFT 16 MM. 7525 = PISTON 75 MM + SHAFT 25 MM.
 362 = PISTON 36 MM + SHAFT 12 MM

DIGIT 7 - OR /

DIGIT 8-10 LENGTH OF SHOCK

DIGIT 11-14 FEATURE

11 P = STEP SPRING PRELOAD



13 C = COMPRESSION ADJUSTABLE



T = THREADED SPRING PRELOAD



W = HIGH-LOW SPEED COMPRESSION ADJUSTABLE



H = HYDRAULIC SPRING PRELOAD



V = VBSC - HIGH-LOW SPEED COMPRESSION AND OIL BALANCE ADJUSTABLE



HI = HYDRAULIC



12 R = REBOUND ADJUSTABLE



14 L = LENGTH ADJUSTABLE



DIGIT 15 - OR /

DIGIT 16-17 SPEC SHEET NUMBER

DIGIT 18 ADDITIONAL

EXAMPLES

Length 280 MM.
 Piston 36 mm.+shaft 12 mm. Thread spring preload
RZ362-280TR-87 Spec sheet No.87
 Rear twin shock Rebound adjustable
 Emulsion gas shock

Piston 30 mm.+shaft 20 mm. Length 400 MM.
FB3020-400-OI Spec sheet No.OI
 Front twin shock Hybrid

Length 340 MM.
 Piston 50 mm.+shaft 16 mm. Hydraulic spring preload
MG506-340HRCL-OIS Classic series
 Rear mono shock Compression adjustable
 Rebound adjustable Length adjustable
 External reservoir piggy back gas shock Spec sheet No.OI

Length 350 MM.
 Piston 55 mm.+shaft 22 mm. VBSC-HIGH-LOW SPEED
FX5022-350V-OI Spec sheet No.OI
 Front twin shock External reservoir on hose gas shock
 COMPRESSION AND OIL BALANCE ADJUSTABLE